

Lotus Digital Wide Dynamic Vari-focal Outdoor IR Color Camera LCIR4035V

FEATURES

- 1/3" SONY Super HAD CCD II sensor.
- Images with high resolution 960H 700TV Lines.
- Built-in OSD Function Control.
- Built-in 2D-DNR to eliminate the noise of the images while promoting the storage space of DVR.
- Built-in ATR(WDR) function to make the image more recognizable when the object is behind the light.
- Built-in High-Power 35pcs IR LED for 40meter range.
- Qualified to IP67 standard with wall mount bracket.



Mounting Bracket included

SPECIFICATIONS

Model No.	LCIR4035V
Image CCD Sensor	1/3" SONY Super HAD CCD II
Picture Elements	NTSC : 1020x508, PAL : 1020x596
Resolution	700TVL
Min. illumination	0.08 Lux@F1.2
Synchronizing system	INTERNAL
Video Output	BNC : 1.0 Vp-p, Composite : 75 Ohms
S/N Ratio	More than 52dB (AGC/Off)
Electronic Shutter	NTSC: 1/60~1/100,000, PAL: 1/50 ~ 1/110,000
Lens type	2.8~12mm Auto-Iris F1.4
OSD	Yes / 9 Languages
Day/Night Mode	Color / B&W / Auto / EXT
WDR	D-WDR
Back light control	HLC / BLC / MASK / Off
Noise Reduction	2D
White Balance	ATW1 / ATW2 / AWC-SET / ANTI CRL / MANUAL
Motion Detection	48 x 15 Zones
Privacy	8 Zones
IR LED	35pcs IR LED
Weatherproof	IP67
Power Supply	DC12V
Power consumption	Max. 6W
Operation Humidity	RH85% or less
Operation Temp.	-10°C ~ +50°C
Dimension (H x L x D)	95 x 89 x 159mm
Weight	1.3Kg (Include Bracket)

** Specifications are subject to change without prior notice