

Lotus Indoor 700TVL 15M IR Dome Camera

LCIR715D




FEATURES

- 1/3" Sony Super HAD CCD II sensor.
- Suitable to install indoor environment with very clear image even in any angle of screen.
- Image position can be adjustable by 3 axis.
- Built-in board lens and 24pcs IR LEDs.
- Built-in Auto electronic shutter.
- Auto White Balance control.
- Illuminating distance to 15 meter.

SPECIFICATIONS

Model	LCIR715D
Image CCD Sensor	1/3" SONY Super HAD CCD II
Picture Elements	NTSC : 1020x508, PAL : 1020x596
H-Resolution	700TVL
Min. illumination	0.08 Lux@F1.2
Scanning system	NTSC : 525 lines, PAL : 625 lines; 2:1 interlace
Video Output	Composite: 1.0 Vp-p, 75 Ohms
S/N Ratio	More than 48dB
Electronic Shutter	NTSC: 1/60~1/100,000. PAL: 1/50 ~ 1/110,000
Lens type	Standard: 3.6mm Lens Option: 4mm, 6mm, 8mm Lens
Back light control	Auto control
White Balance	Auto control
IR LED	24pcs IR LED, 15 meter
Power Supply	DC12V / 500mA
Power consumption	Max. 3.3W
Operation Humidity	RH85% or less
Operation Temp.	-20°C ~ +50°C
Dimension(H x L x D)	106.1 x 142.5 x 100.5mm
Weight	0.4Kg

Dimension (mm)



** Specifications are subject to change without prior notice