## **Lotus Outdoor Color IR Vandal Dome Camera**



## LCIR725VD

## FEATURES

- •1/3" Sony Super HAD CCD II sensor.
- Suitable to install outdoor environment with very clear image even in any angle of screen.
- Image position can be adjustable by 2 axis.
- Built-in board lens and 21pcs IR LEDs.
- Built-in Auto electronic shutter.
- Auto White Balance control.
- Qualified to IP66 standard
- Illuminating distance to 20 meter.



## SPECIFICATIONS

| Model              | LCIR725VD  |
|--------------------|--|
| Image CCD Sensor   | 1/3" SONY Super HAD CCD II                       |
| Picture Elements   | NTSC: 1020x508, PAL: 1020x596                    |
| H-Resolution       | 700TVL   |
| Min. illumination  | 0.08 Lux @ F1.2                                  |
| Video Output       | Composite: 1.0 Vp-p, 75 Ohms                     |
| S/N Ratio          | More than 52dB (AGC/Off)                         |
| Electronic Shutter | NTSC: 1/60~1/100,000, PAL: 1/50 ~ 1/100,000      |
| Lens type          | Standard: 3.6mm Lens Option: 6mm, 8mm, 12mm Lens |
| OSD                | Yes / 9 Languages                                |
| Day/Night Mode     | Color / B&W / Auto / EXT                         |
| WDR                | D-WDR  |
| Back light control | HLC / BLC / MASK / Off                           |
| White Balance      | ATW1/ATW2/AWC-SET/ANTI CRL/ Manual               |
| IR LED             | 21 pcs IR LEDs, 20 meter                         |
| Weatherproof       | IP66   |
| Power Supply       | DC12V / 500mA                                    |
| Power consumption  | Max. 3.3W  |
| Operation Humidity | RH85% or less                                    |
| Operation Temp.    | -20°C ~ +50°C                                    |
| Dimension          | 108mm(D) x 80mm(H)                               |
| Weight             | 380g   |

<sup>\*\*</sup> Specifications are subject to change without prior notice