

LDVR818 Digital Video Recorder

8-Channel 960H H.264 Digital Video Recorder with POS

LDVR818 is new standalone digital video recorder (DVR) for use in residential and retail surveillance installations.

960H represents the number of horizontal pixels in the CCD image sensor and provides a 30% increase in resolution in comparison to D1. The greater the resolution, the higher the definition of the video image. 960H DVR is a must to complement the 960H camera to realize the high resolution video.

This DVR supports up to 3TB HDD for recording time. POS support makes this DVR ideal for retail and hospitality applications.

Features:

• 960H resolution

With previous D1 DVRs, although you may have a 650TVL analog camera, you can only record at D1 resolution which can clearly discern only up to 540TVL. With the new 960H DVR, not only can it capture high-resolution 700TVL cameras, but it can also enhance the recording quality of the existing cameras as its full resolution of up to 700TVL will be realized.

3D De-interlace

Live stream video is enhanced by the 3D De-interlace function, providing high quality images.

Hyper Interactive E-Map

LDVR818 features a Hyper E-map function, allowing users to customize E-map and E-map objects to fulfill customize needs. It provides multi-task managerial functions through unlimited E-map layers.

• 3G/GPRS Mobile Phone Surveillance

LDVR818 provides remote surveillance with 3G/GPRS mobile phone or PDA phone, without additional software.


Smart Detection Zone Search

LDVR818 allows users to specify a certain region of the camera video. If any event will be listed. This help locate events of interest very efficiently.



CE F© RoHS ISO 9001:2000

System Configuration



System	LDVR818 960H	Digital Video Recorder	
System	System	System	Embedded Linux
Video Output		Mode	Multiplex – Live, Record, Network, Backup, Remote access, Control, Playback
Video Output		Video Channel	8 Channels
Alarm Input		Video Output	BNC x 1,VGA x1, HDM! x1
Alarm Output 1 Output 1 Output Compression H.264 - Vicleo,: ADPCM - audio Display Resolution NTSC: 960x480(30), PAL:960x576 (25) 960H: 180/150fps; D1/Half D1/CIF: 240 / 200fps Pecord Display Division 1,4,7,8 Playback Mode Vicleo Loss, Event, Date/Time, Smart Search Playback Operation Play, Fast Forward, Backward, Pause, Stop, Slow Digital Zoom 2x, 4x CMS, IEBrowser Network Interface 1 RJ-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPOE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User Amangement 4 DVRS Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS POS needs RS-485 to RS-232 converter, not included) USB USB USB DC 12V Power Consumption 24W Max		Audio	2 RCA-jack connectors / 1 RCA-jack connectors
Compression H.264 - Video,: ADPCM - audio Display Resolution NTSC: 960x480(30), PAL:960x576 (25) Record 960H: 180/150fps; D1/Half D1/CIF: 240 / 200fps Recording Mode Manual / Schedule/ Motion / Alarm Display Division 1,4,7,8 Playback Mode Video Loss, Event, Date/Time, Smart Search Playback Operation Play, Fast Forward, Backward, Pause, Stop, Slow Digital Zoom 2x, 4x Software CMS, IEBrowser Network Interface 1 1,8-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User 6 Max Management 4 DVRs Control / Management PTZ / e-MAP/ GPS system / POS (POS needs RS-485 to RS-232 converter, not included) Storage / Backup USB 1 USB port support DVD+RW, DVD+R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Supply DC 12V Power Consumption 24W Max		Alarm Input	4 Input
Display Resolution NTSC: 960x480(30), PAL:960x576 (25) Record 950H: 180/150fps; D1/Half D1/CIF : 240 / 200fps Recording Mode Manual / Schedule/ Motion / Alarm Display Division 1,4,7,8 Playback Mode Video Loss, Event, Date/Time, Smart Search Playback Operation Play, Fast Forward, Backward, Pause, Stop, Slow Digital Zoom 2x, 4x Software CMS, IEBrowser Network Interface 1 RJ-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User 6 Max Management 4 DVRs Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS Yes (POS needs RS-485 to RS-232 converter, not included) RS-485 Yes Internal Storage 3.5" SATA HDD x 1, 3TB Max USB 1 USB port support DVD+RW, DVD-R, Card readers, HDD, 1 USB port for mouse Power Supply DC 12V Power Consumption 24W Max		Alarm Output	1 Output
Record 960H: 180/150fps; D1/Half D1/CIF: 240 / 200fps Recording Mode Manual / Schedule/ Motion / Alarm Display Division 1,4,7,8 Playback Mode Video Loss, Event, Date/Time, Smart Search Playback Operation Play, Fast Forward, Backward, Pause, Stop, Slow Digital Zoom 2x, 4x Software CMS, IEBrowser Network Interface 1 RJ-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP Audio 2 Way Remote User 6 Max Management 4 DVRs Operation Interface Mouse / Keypad / Remote Controller (included) Yes (POS needs RS-485 to RS-232 converter, not included) Yes (POS needs RS-485 to RS-232 converter, not included) RS-485 Yes (POS needs RS-485 to RS-232 converter, not included) Yes (POS needs RS-485 to RS-232 converter, not included) USB Internal Storage 3.5" SATA HDD x 1, 3TB Max USB port support DVD+RW, DVD+R, Card readers, HDD, 1 USB port for m	Video	Compression	H.264 - Video,: ADPCM - audio
Video Recording Mode Display Division Display Division Display Division Display Division Display Division Digital Zoom Di		Display Resolution	NTSC: 960x480(30), PAL:960x576 (25)
Display Division 1,4,7,8 Playback Mode Video Loss, Event, Date/Time, Smart Search Playback Operation Play, Fast Forward, Backward, Pause, Stop, Slow Digital Zoom 2x,4x Software CMS, IEBrowser Network Interface 1 RJ-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User 6 Max Management 4 DVRs Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS Yes (POS needs RS-485 to RS-232 converter, not included) RS-485 Yes Internal Storage 3.5" SATA HDD x 1, 3TB Max Storage / Backup Dimension 290(W) x 240(D) x 58(H)mm Power Supply DC 12V Power Consumption 24W Max			D1/Half D1/CIF: 240 / 200fps
Display Division 1,4,7,8 Playback Mode Video Loss, Event, Date/Time, Smart Search Playback Operation Play, Fast Forward, Backward, Pause, Stop, Slow Digital Zoom 2x,4x Software CMS, IEBrowser Network Interface 1 RJ-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User 6 Max Management 4 DVRs Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS Total Internal Storage 3.5" SATA HDD x 1, 3TB Max USB 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Consumption 24W Max		Recording Mode	Manual / Schedule/ Motion / Alarm
Playback Operation Play, Fast Forward, Backward, Pause, Stop, Slow Digital Zoom 2x ,4x Software CMS, IEBrowser Network Interface 1 RJ-45 10/100 baseT Ethernet connector TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User 6 Max Management 4 DVRS Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS Yes (POS needs RS-485 to RS-232 converter, not included) RS-485 Yes Internal Storage 3.5" SATA HDD x 1, 3TB Max USB 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Supply DC 12V Power Consumption 24W Max		Display Division	1,4,7,8
Digital Zoom 2x,4x Software CMS, IEBrowser Network Interface 1 RJ-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User 6 Max Management 4 DVRs Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS Internal Storage Storage / Backup Dimension 290(W) x 240(D) x 58(H)mm Power Supply Power Consumption 224W Max		Playback Mode	Video Loss, Event, Date/Time, Smart Search
Network Software CMS, IEBrowser Network Interface 1 RJ-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User 6 Max Management 4 DVRs Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS RS-485 Yes Internal Storage 3.5" SATA HDD x 1, 3TB Max Storage / Backup USB 1 USB port support DVD+RW, DVD+R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Supply DC 12V Power Consumption 24W Max Power Supply DC 12V Power Consumption 24W Max Power Supply DC 12V Power Supply DC 12V Power Supply DC 12V Power Supply DC 12V Power Consumption 24W Max Power Supply DC 12V P			Play, Fast Forward, Backward, Pause, Stop, Slow
Network Interface 1 RJ-45 10/100 baseT Ethernet connector Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP Audio 2 Way Remote User 6 Max Management 4 DVRs Control / Management Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS Yes (POS needs RS-485 to RS-232 converter, not included) RS-485 Yes Internal Storage 3.5" SATA HDD x 1, 3TB Max USB 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Consumption 24W Max		Digital Zoom	2x ,4x
Network Protocol Audio Remote User Ananagement Operation Interface PTZ / e-MAP/ GPS system / POS Internal Storage Internal Storage Dimension Power Protocol TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP 2 Way 6 Max Mouse / Keypad / Remote Controller (included) Yes (POS needs RS-485 to RS-232 converter, not included) Yes Yes 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse Dimension Power Supply Power Consumption 24W Max	Network		
Audio 2 Way Remote User 6 Max Management 4 DVRs Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS (POS needs RS-485 to RS-232 converter, not included) RS-485 Yes Internal Storage 3.5" SATA HDD x 1, 3TB Max USB 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Supply DC 12V Power Consumption 24W Max		Network Interface	1 RJ-45 10/100 baseT Ethernet connector
Audio Remote User Management Operation Interface FTZ / e-MAP/ GPS system / POS RS-485 Internal Storage USB Dimension Audio Remote User Mouse / Keypad / Remote Controller (included) Yes (POS needs RS-485 to RS-232 converter, not included)		Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP,TSP
Management 4 DVRs Operation Interface Mouse / Keypad / Remote Controller (included) PTZ / e-MAP/ GPS system / POS RS-485 Yes Internal Storage Just Just Just Just Just Just Just Just		7 (0.0.10	•
Control / Management Operation Interface PTZ / e-MAP/ GPS system / POS RS-485 Internal Storage USB Dimension Power Operation Interface Mouse / Keypad / Remote Controller (included) Yes (POS needs RS-485 to RS-232 converter, not included) Yes 1 Yes 3.5" SATA HDD x 1, 3TB Max 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse DIMENSION Power Supply Power Consumption DC 12V Power Consumption 24W Max			
Control / Management PTZ / e-MAP/ GPS system / POS RS-485 Internal Storage USB Dimension 290(W) x 240(D) x 58(H)mm Power Power Power Power Power Power Possible (POS needs RS-485 to RS-232 converter, not included) Yes Yes Yes 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse DC 12V Power Consumption Power Consumption Power Supply Power Consumption Possible (POS needs RS-485 to RS-232 converter, not included) Yes Yes Yes Yes 1 USB port support DVD+RW, DVD-R, Card readers, HDD, 1 USB port for mouse DC 12V Power Consumption 24W Max			4 DVRs
Control / Management P1Z / e-MAP / GPS system / POS included) RS-485 Yes Internal Storage 3.5" SATA HDD x 1, 3TB Max USB 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Supply DC 12V Power Consumption 24W Max	Control / Management	Operation Interface	Mouse / Keypad / Remote Controller (included)
Storage / Backup Internal Storage USB USB 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Supply Power Consumption DC 12V Power Consumption 24W Max		PTZ / e-MAP/ GPS system / POS	
Storage / Backup USB 1 USB port support DVD+RW, DVD+R, DVD-R, Card readers, HDD, 1 USB port for mouse 290(W) x 240(D) x 58(H)mm Power Supply Power Consumption 1 USB port support DVD+RW, DVD-R, Card readers, HDD, 1 USB port for mouse DC 12V 24W Max		RS-485	Yes
Storage / Backup USB 1 USB port support DVD+RW, DVD-R, Card readers, HDD, 1 USB port for mouse Dimension 290(W) x 240(D) x 58(H)mm Power Supply Power Consumption 1 USB port support DVD+RW, DVD-R, Card readers, HDD, 1 USB port for mouse DC 12V 24W Max	Storage / Backup	Internal Storage	3.5" SATA HDD x 1, 3TB Max
Power Supply DC 12V Power Consumption 24W Max			
Power Consumption 24W Max	Dimension	290(W) x 240(D) x 58(H)mm	
Power Consumption 24W Max	Power	Power Supply	DC 12V
<u>'</u>		Power Consumption	24W Max
Temperature 0°C ~ +45°C (Operation)	Temperature	0°C ~ +45 °C (Operation)	

Specification are subject to change without prior notice.